PRODUCT DATA SHEET

Model: **PZAT7D**

Packaged Air-Cooled
7 Ton Chiller

LEGACY CHILLER SYSTEMS

Legacy Chiller Systems
851 Tech Drive
Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Intertek

Side/Front View

STANDARD ON ALL LEGACY CHILLER MODELS:
Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display. (located inside electrical cabinet)

Back View

Standard Features:

- **ETL listed** to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- **Single point power connection**
- **Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display**
- **STAINLESS STEEL** Tank
- **STAINLESS STEEL**, brazed plate evaporator
- **Scroll** compressor with crankcase heater
- **Suction accumulator**
- **Water flow switch**
- **Hot gas by-pass capacity control**
- **24V control transformer**
- Direct drive condenser fan motor
- Rust resistant, high CFM, aluminum condenser fan blade
- Condenser(s): copper tube/aluminum fin
- Compressor motor contactor
- Condenser motor and control circuit fusing
- **Painted (Powder Coated), galvanized sheet metal cabinet**
- 1/2" insulation on all water and Low pressure refrigerant lines
- Liquid line drier, sight glass, solenoid,TXV
- Complete refrigerant charge from factory
- **Factory Performance Test prior to shipment**
- **Extended warranty:** See your quote or latest IOM booket revision

Easy to Use Touch Screen Display on all Legacy Chiller Models

Options:

- **Copeland Digital Scroll Compressor**
- **Remote Idec touchscreen control panel**
- **Industrial VPN Router**
- **5 Port Ethernet Switch**
- **BacNet Gateway**
- **Process Pump VFD Controller**
- **VFD Compressor Control**
- 4 year extended compressor warranty
- Casters (factory mounted)
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and High/Low voltage
- Compressor fusing
- Tank Sight Glass
- Compressor Sound Cover
- Flooded cond. w/receiver/head pressure control (0°F)
- Heated, flooded cond. w/receiver/head pressure Water flow meter control (-20°F)
- Dual process pump with auto changeover
- Pump suction isolation valve
- Water pressure gauge set
- Copper finned condenser coil (coastal protection)
- Coastal powder coat paint protection
- E-Coat Condenser Coil (coastal protection)
- Water Flow Meter
- Auto city water make up solenoid & auto level switch
- Auto city water changeover panel with filter
- Storage tank sight glass
- Door Mounted HMI with weather proof cover

© Property of Legacy Chiller Systems, Inc.

PRODUCT DATA SHEET

Model: **PZAT7D**

Packaged Air-Cooled
7 Ton Chiller

Legacy Chiller Systems
851 Tech Drive
Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Dual Circuit)

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA ea.	LRA ea.	Fan Motor		Recirculation Pump	MCA	M.O.P	Reservoir Gal.	Chiller Fluid Conn.	Weight Pounds
				Voltage	Phase	Freq.	Qty.	HP			Qty.	FLA.						
PZAT7DE5	75	34	76	208/230V	1	60Hz	2	4	21.8	137	2	3.8	6.6	70	80	50	1.25" FPT	1100
PZAT7DF5				208/230V	3	60Hz			15.4	114		3.8	6.6	50	60			
PZAT7DH5				460V	3	60Hz			7.1	58		1.5	1.7	25	25			
PZAT7DI5				575V	3	60Hz			5.2	43		1.72	1	20	20			

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
7D	ZS29KAE	***42.0**	6.3	7.1	9.8	5.9	7.8	8.7	5.8	8.2	8.2	5.6	8.5	7.7	5.4	8.9	7.2
		***44.0**	6.5	7.2	10.1	6.2	7.9	9.0	**6.0**	**8.3**	**8.5**	5.9	8.6	7.9	5.7	9.0	7.5
		45.0	6.7	7.3	10.3	6.3	7.9	9.1	6.2	8.3	8.6	6.0	8.7	8.0	5.8	9.1	7.6
		50.0	7.4	7.4	10.9	7.0	8.1	9.7	6.7	8.4	9.1	6.6	8.8	8.6	6.4	9.2	8.1

* = Requires the use of glycol.

Intertek

Product Dimensional Drawing



© Property of Legacy Chiller Systems, Inc.