PRODUCT DATA SHEET

Model: PZAT9S

Packaged Air-Cooled 9 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank



Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2
 No. 236-11, 4th edition, 10/14/2011
- Single point power connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL Tank
- Fused, STAINLESS STEEL recirculation pump for tank
- STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction accumulator
- · Water flow switch
- · Hot gas by-pass capacity control
- 24V control transformer
- Direct drive condenser fan motor
- Rust resistant, high CFM, aluminum condenser fan blade
- Condenser(s): copper tube/aluminum fin
- Compressor motor contactor
- Condenser motor and control circuit fusing
- Painted (Powder Coated), galvanized sheet metal cabinet
- 1/2" insulation on all water and Low pressure refrigerant lines
- · Liquid line drier, sight glass, solenoid,TXV
- · Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Easy to Use Touch Screen Display on all Legacy Chiller Models



Options:

- Copeland Digital Scroll Compressor (Hot Gas Bypass Removed)
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- STAINLESS STEEL Process Pump
- Process Pump VFD Controller
- VFD Compressor Control (Hot Gas Bypass Removed)
- 4 year extended compressor warranty
- Casters (factory mounted)
- 115 volt (rain tight) service outlet
- · Non Fused Disconnect
- · Phase/voltage monitor
- Compressor fusing
- Tank Sight Glass
- Compressor Sound Cover
- Flooded cond. w/receiver/head pressure control (0°F)
- Flooded cond. w/Heated receiver/head pressure control (-20°F)
- · Dual process pumps with auto changeover
- Pump suction isolation valve(s)
- · Water pressure gauge set
- Copper finned condenser coil (coastal protection)
- · Coastal powder coat paint protection
- E-Coat Condenser Coil (coastal protection)
- Water Flow Meter
- · Auto city water make up solenoid & auto level switch
- Auto city water changeover panel with filter
- Door Mounted HMI with weather proof cover

PRODUCT DATA SHEET

Model: PZAT9S

Packaged Air-Cooled 9 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Single Circuit)

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA	LRA	Fan Motor		Recirculation			Reservoir	Chiller	Weight
				Voltage	Phase	Freq.	Qty.	НР	ea.	ea.	Qty.	FLA.	Pump FLA	MCA	M.O.P	Gal.	Fluid Conn.	Pounds
PZAT9SF5			76	208/230V	3	60Hz	1	10	37.2	239	2	3.8	7.9	70	90	80	1.25" FPT	1150
PZAT9SH5	75	34		460V	3	60Hz			17.2	125		1.5	2.5	30 25	40			
PZAT9SI5				575V	3	60Hz			12.4	80		1.72	1.5		30			

* = Requires the use of glycol. Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
98	ZB76KCE	*42.0	8.0	8.4	10.8	7.8	9.2	9.6	7.6	9.7	9.0	7.3	10.1	8.4	7.0	10.6	7.9
		*44.0	8.4	8.5	11.1	8.1	9.3	9.8	7.9	9.7	9.2	7.6	10.2	8.7	7.4	10.7	7.2
		45.0	8.5	8.6	11.3	8.3	9.3	10.0	8.1	9.8	9.4	7.9	10.3	8.9	7.6	10.7	7.3
		50.0	9.5	8.7	12.0	9.2	9.5	10.7	8.9	10.0	10.0	7.7	10.5	9.4	8.4	10.9	7.9

- 1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
- 2. KW input is for compressor(s) only.
- 3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.



