# PRODUCT DATA SHEET

Model: **PZW10D**Packaged Water-Cooled

10 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

### STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC)
with HMI Touch Screen Display.

User-Friendly
Touch Screen
Display

Process
Fluid Inlet
Cabinet

Process \_ Fluid Outlet

#### Front View

## **Standard Features:**

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- · STAINLESS STEEL, brazed plate evaporator

Front/Side View

- · Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- · Control circuit fusing
- Condenser(s): Coaxial up to PZW22D
- Condenser(s): Shell and Tube PZW26D through PZW52D
- · Compressor motor contactor
- Painted Powder Coated (up to PZW22D), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Easy to Use Touch Screen Display on all Legacy Chiller Models



# **Options:**

- Copeland Digital Scroll Compressor
- · Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- Casters (factory mounted)
- · Condenser water regulating valve
- 115 volt (rain tight) service outlet
- · Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- · Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- · Pump suction isolation valve
- Water pressure gauge set
- · Water Flow Meter
- · Auto city water changeover panel with filter
- Door Mounted HMI with weather proof cover

# ODUCT DATA SHEET

Model: PZW10D

Packaged Water-Cooled 10 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

### **Dimensional & Electrical Table (Dual Circuit)**

| Chiller<br>Models | Length<br>Inches | Width<br>Inches | Height<br>Inches | Power    |       | Compressor |      | RLA | LRA  |     |     | Chiller | Weight         |        |
|-------------------|------------------|-----------------|------------------|----------|-------|------------|------|-----|------|-----|-----|---------|----------------|--------|
|                   |                  |                 |                  | Voltage  | Phase | Freq.      | Qty. | НР  | ea.  | ea. | MCA | M.O.P   | Fluid<br>Conn. | Pounds |
| PZW10DF5          | 65               | 34              | 37               | 208/230V | 3     | 60Hz       | 2    | 6   | 18.6 | 156 | 45  | 60      | 1.25"<br>FPT   | 800    |
| PZW10DH5          |                  |                 |                  | 460V     | 3     | 60Hz       |      |     | 10.3 | 75  | 25  | 30      |                |        |
| PZW10DI5          |                  |                 |                  | 575V     | 3     | 60Hz       |      |     | 7.1  | 54  | 20  | 20      |                |        |

## **Capacity Table (Refrigerant R407C)**

| Model | Сотписаток | LWT  | 105°F Condensing |     |      |  |  |
|-------|------------|------|------------------|-----|------|--|--|
| Wodei | Compressor | °F   | TONS             | KW  | EER  |  |  |
|       |            | 42.0 | 10.4             | 9.1 | 14.2 |  |  |
| 400   | ZB45KCE    | 44.0 | 10.8             | 9.1 | 14.8 |  |  |
| 10D   | ZB43NGE    | 45.0 | 11.1             | 9.1 | 15.0 |  |  |
|       |            | 50.0 | 12.2             | 9.2 | 16.5 |  |  |

- 1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
- 2. KW input is for compressor(s) only.

  3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.



# **Product Dimensional Drawing**









