# PRODUCT DATA SHEET

Model: PZW13D

Packaged Water-Cooled 13 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969


Toll-Free: (877) 988-5464

#### STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.



Electrical Panel Open



### **Standard Features:**

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- · STAINLESS STEEL, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- · Control circuit fusing
- Condenser(s): Coaxial up to PZW22D
- Condenser(s): Shell and Tube PZW26D through PZW52D
- Compressor motor contactor
- Painted Powder Coated (up to PZW22D), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Easy to Use **Touch Screen Display** on all Legacy Chiller Models



## Options:

- Copeland Digital Scroll Compressor
- · Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- Casters (factory mounted)
- · Condenser water regulating valve
- 115 volt (rain tight) service outlet
- · Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- · Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- · Pump suction isolation valve
- · Water pressure gauge set
- Water Flow Meter
- · Auto city water changeover panel with filter
- Door Mounted HMI with weather proof cover

# ODUCT DATA SHEET

Model: PZW13D

Packaged Water-Cooled 13 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

### **Dimensional & Electrical Table (Dual Circuit)**

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA	LRA			Chiller	Weight
				Voltage	Phase	Freq.	Qty.	НР	ea.	ea.	MCA	M.O.P	Fluid Conn.	Pounds
PZW13DF5	75	34	37	208/230V	3	60Hz	2	8	28.8	195	70	90	1.25" FPT	900
PZW13DH5				460V	3	60Hz			14.7	95	35	45		
PZW13DI5				575V	3	60Hz			10.8	80	25	35		

### Capacity Table (Refrigerant R407C)

Madel	Сотписасон	LWT	105°F Condensing				
Model	Compressor	°F	TONS	KW	EER		
13D		42.0	13.5	12.0	14.0		
	ZB58KCE	44.0	14.1	12.0	14.6		
	ZBOOKUE	45.0	14.4	12.0	14.9		
		50.0	16.0	12.0	16.5		

- 1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
- 2. KW input is for compressor(s) only.

  3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.



### **Product Dimensional Drawing**

