PRODUCT DATA SHEET

Model: **PZW7S**Packaged Water-Cooled

7 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464



Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- Control circuit fusing
- Condenser(s): Coaxial up to PZW22D
- Condenser(s): Shell and Tube PZW26D through PZW52D
- Compressor motor contactor
- Painted Powder Coated (up to PZW22D), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Easy to Use Touch Screen Display on all Legacy Chiller Models



Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- · Casters (factory mounted)
- · Condenser water regulating valve
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- · Compressor fusing
- · Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- · Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- · Pump suction isolation valve
- · Water pressure gauge set
- · Water Flow Meter
- Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI with weather proof cover

DUCT DATA SHEET

Model: PZW7S

Packaged Water-Cooled 7 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

Dimensional & Electrical Table (Single Circuit)

| Chiller Models | Length Inches | Width Inches | Height Inches | Power | | | Compressor | | RLA | LRA | | | Chiller | Weight |
|-------------------|------------------|-----------------|------------------|----------|-------|-------|------------|----|------|-----|-----|-------|----------------|--------|
| | | | | Voltage | Phase | Freq. | Qty. | НР | ea. | ea. | MCA | M.O.P | Fluid Conn. | Pounds |
| PZW7SF5 | 46 | 34 | 36 | 208/230V | 3 | 60Hz | | 8 | 28.8 | 195 | 40 | 60 | 1.25" FPT | 525 |
| PZW7SH5 | | | | 460V | 3 | 60Hz | 1 | | 14.7 | 95 | 20 | 30 | | |
| PZW7SI5 | | | | 575V | 3 | 60Hz | | | 10.8 | 80 | 15 | 20 | | |

Capacity Table (Refrigerant R407C)

| Model | Compressor | LWT | 105°F Condensing | | | | |
|-------|------------|------|------------------|------|------|--|--|
| Wodei | Compressor | °F | TONS | KW | EER | | |
| 7\$ | | 42.0 | 6.75 | 5.98 | 14.0 | | |
| | ZB58KCE | 44.0 | 7.06 | 5.99 | 14.6 | | |
| | ZDJOKCE | 45.0 | 7.21 | 5.99 | 14.9 | | |
| | | 50.0 | 7.99 | 6.00 | 16.5 | | |

- 1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
- KW input is for compressor(s) only.
 EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.



Product Dimensional Drawing











