# PRODUCT DATA SHEET

Model: PZWT13D

Packaged Water-Cooled
13 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

#### STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.



### **Standard Features:**

- ETL listed to UL1995 & CAN/CSA C22.2
   No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- · Data Recording Memory Card
- STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- Control circuit fusing
- · Condenser(s): Coaxial up to PZW22D
- Condenser(s): Shell and Tube PZW26D through PZW52D
- · Compressor motor contactor
- Painted Powder Coated (Most Models), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory


#### **Tank**

- STAINLESS STEEL storage tank with 1/2 inch insulation
- Fused, STAINLESS STEEL re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Easy to Use
Touch Screen Display on all
Legacy Chiller Models



## with Stainless Steel Tank



- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- Casters (factory mounted)
- Condenser water regulating valve
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- · Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI with weather proof cover

#### **Tank Options**

- Storage tank sight glass
- Tank low liquid level indicator with dry contacts

# PRODUCT DATA SHEET

Model: PZWT13D

Packaged Water-Cooled 13 Ton Chiller



Legacy Chillers, Inc.

851 Tech Drive Telford, PA 18969


Toll-Free: (877) 988-5464

#### **Dimensional & Electrical Table (Dual Circuit)**

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA	LRA	Recirculation			Reservoir	Chiller	Weight
				Voltage	Phase	Freq.	Qty.	HP	ea.	ea.	Pump FLA	MCA	M.O.P	Gal.	Fluid Conn.	Pounds
PZWT13DF5	75	34	70	208/230V	3	60Hz	2	8	28.8	195	5.0	70	90	80	1.5" 1300 FPT	
PZWT13DH5				460V	3	60Hz			14.7	95	2.5	40	50			1300
PZWT13DI5				575V	3	60Hz			10.8	80	1.8	30	35			

#### **Capacity Table (Refrigerant R407C)**

Model	Самичасац	LWT	105°F Condensing				
Wodel	Compressor	°F	TONS	KW	EER		
		*42.0	12.0	12.0	14.0		
13D	ZB58KCE	*44.0	12.6	12.0	14.6		
130	ZDJONGE	45.0	12.8	12.0	14.9		
		50.0	14.3	12.0	16.5		



1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.

**Product Dimensional Drawing** 

- KW input is for compressor(s) only.
   EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.

