PRODUCT DATA SHEET

Model: PZAT22D

Packaged Air-Cooled
22 Ton Chiller



Legacy Chiller Systems

22115 NW Imbrie Dr, Ste 398 Hillsboro, OR 97124

Toll-Free: (877) 988-5464

STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display. (located inside electrical cabinet)

> Electrical Cabinet



Process Fluid In & Process Fluid Out Conections located on the back side.



with
Stainless Steel
Tank

Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2
 No. 236-11, 4th edition, 10/14/2011
- Single point power connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL Tank
- STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction accumulator
- Water flow switch
- · Hot gas by-pass capacity control
- 24V control transformer
- Direct drive condenser fan motor
- Rust resistant, high CFM, aluminum condenser fan blade
- Condenser(s): copper tube/aluminum fin
- Compressor motor contactor
- · Condenser motor and control circuit fusing
- Painted (Powder Coated), galvanized sheet metal cabinet
- 1/2" insulation on all water and Low pressure refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment
- Extended warranty: See your quote or latest IOM booket revision

Easy to Use Touch Screen Display on all Legacy Chiller Models

Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- · 4 year extended compressor warranty
- Casters (factory mounted)
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and High/Low voltage
- Compressor fusing
- Tank Sight Glass
- Compressor Sound Cover
- Flooded cond. w/receiver/head pressure control (0°F)
- Heated, flooded cond. w/receiver/head pressure Water flow meter control (-20°F)
- · Dual process pump with auto changeover
- Pump suction isolation valve
- · Water pressure gauge set
- Copper finned condenser coil (coastal protection)
- Coastal powder coat paint protection
- E-Coat Condenser Coil (coastal protection)
- · Water Flow Meter
- Auto city water make up solenoid & auto level switch
- · Auto city water changeover panel with filter
- Storage tank sight glass
- · Door Mounted HMI with weather proof cover

PRODUCT DATA SHEET

Model: PZAT22D

Packaged Air-Cooled 22 Ton Chiller



Legacy Chiller Systems 22115 NW Imbrie Dr, Ste 398 Hillsboro, OR 97124

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Dual Circuit)

Chiller Models	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA	LRA	Fan Motor		Recirculation		Reservoir	Chiller	Weight	
				Voltage	Phase	Freq.	Qty.	НР	ea.	ea.	Qty.	FLA.	Pump FLA	MCA	M.O.P	Gal.	Fluid Conn.	Pounds
PZAT22DF5		65	77	208/230V	3	60Hz	2	13	49.4	300	4	3.8	3.5	150	175	120	1.5" FPT	1450?
PZAT22DH5	75			460V	3	60Hz			23.1	150		1.5	1.7	60 60	80			
PZAT22DI5				575V	3	60Hz			19.2	109		1.72	1.0		70			

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	80°F			90°F			95°F			100°F			105°F		
			TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
22D	ZB95KCE	42.0	20.9	18.0	12.0	20.0	19.8	10.5	19.4	20.8	9.8	18.9	21.8	9.2	18.5	23.0	8.5
		44.0	21.7	18.2	12.3	20.7	20.0	10.7	20.1	21.0	10.0	19.7	22.0	9.4	19.2	23.2	8.8
		45.0	22.1	18.2	12.5	21.0	20.1	10.9	20.5	21.1	10.2	20.0	22.2	9.6	19.6	23.3	8.9
		50.0	23.8	18.8	13.1	22.8	20.6	11.6	22.1	21.6	10.8	21.7	22.6	10.2	21.3	23.7	9.5

* = Requires the use of glycol.



Product Dimensional Drawing

*Changes or Modifications Subject to Factory Discretion.

