PRODUCT DATA SHEET

Model: **PZW1S** Packaged Water-Cooled 1 Ton Chiller



STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC)

with HMI Touch Screen Display.

Legacy Chillers, Inc. 851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

User-Friendly

Touch Screen

Display

LEGACY CHILLERS



Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL, brazed plate evaporator
- · Scroll compressor with crankcase heater
- Suction Accumulator
- Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- Control circuit fusing
- Condenser(s): Coaxial up to PZW22D
- Condenser(s): Shell and Tube PZW26D through PZW52D
- Compressor motor contactor
- Painted Powder Coated (up to PZW22D), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- · Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Easy to Use Touch Screen Display on all Legacy Chiller Models



Options:

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel

Front View

- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- · Casters (factory mounted)
- Condenser water regulating valve
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- · Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI with weather proof cover

(



PRODUCT DATA SHEET

Model: **PZW1S** Packaged Water-Cooled 1 Ton Chiller



Legacy Chillers, Inc. 851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

Dimensional & Electrical Table (Single Circuit)

	Chiller Models	Length Inches	Width Inches	Height Inches	Power		Compressor		RLA	LRA			Chiller	Weight	
					Voltage	Phase	Freq.	Qty.	HP	ea.	ea.	MCA	M.O.P	Fluid Conn.	Pounds
	PZW1SE5	36	34	36	208/230V	1	60Hz	1	1.3	8.3	40.3	15	15	1" FPT	210

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT	105°F Condensing				
woder	Compressor	°F	TONS	KW	EER		
		42.0	1.05	1.10	11.9		
1S	ZR16K5E	44.0	1.10	1.10	12.5		
13	ZRIONJE	45.0	1.13	1.10	12.8		
		50.0	1.26	1.10	14.4		


1. Capacities on this chart are based on refrigerant R407C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.


2. KW input is for compressor(s) only

3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.




Product Dimensional Drawing





BACK VIEW





ACCESS PANEL

LEFT SIDE VIEW

