PRODUCT DATA SHEET

Model: PZWPT9S

Packaged Water-Cooled
Portable 9 Ton Chiller



Legacy Chiller Systems

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

STANDARD ON ALL LEGACY CHILLER MODELS:

Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.





Standard Features:

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- · STAINLESS STEEL, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction accumulator
- Noncorrosive polyethylene storage tank with 1/2" insulation
- Fused, STAINLESS STEEL Process pump with discharge ball valve
- · Low flow by-pass valve
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- · Rust resistant, high CFM, aluminum condenser fan blade
- Condenser (Water cooled): Coaxial Steel tube / Copper tube
- · Compressor motor and process pump contactors
- · Process pump and control circuit fusing
- Casters (factory mounted)
- Painted (Powder Coated), galvanized sheet metal cabinet
- 1/2" insulation on all water and Low pressure refrigerant lines
- · Liquid line drier, sight glass, solenoid, TXV
- · Complete refrigerant charge from factory
- Factory Performance Test prior to shipment
- Extended warranty: See your quote or latest IOM booket revision

Easy to Use Touch Screen Display on all Legacy Chiller Models



Options:

- · Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Controller
- 4 year extended compressor warranty
- · 115 volt (rain tight) service outlet
- Fused Disconnect
- · Non Fused Disconnect
- Phase monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- · Compressor fusing
- · Compressor sound cover
- Factory installed evaporator heat tape freeze protection
- · Process pump suction isolation valve
- · Water pressure gauge set
- Stainless steel, SCH80 PVC or Polypropylene piping for de-ionized and reverse osmosis water systems
- · Storage Tank Sight Glass
- · Tank low fluid level indicator
- Tank auto city water make up solenoid & auto level switch
- Condenser water regulating valve (Water Cooled Models)
- · Coastal powder coat paint protection
- Custom powder coat paint color scheme (Company Colors & more)
- · Weather Proof HMI Cover

PRODUCT DATA SHEET

Model: PZWPT9S

Packaged Water-Cooled
Portable 9 Ton Chiller



Legacy Chiller Systems
851 Tech Drive

851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

Dimensional & Electrical Table (Single Circuit)

| | | Length Inches | Width Inches | Height Inches | Power | | | Compressor | | | | Process | | | Process | | Chiller | Condenser | |
|-------------------|---------|------------------|-----------------|------------------|----------|-------|------|------------|------------|------------|-------------|---------|-------|------------|-------------------|----------------|----------------|------------------|-----|
| Chiller Models | Voltage | | | | Phase | Freq. | Qty. | НР | RLA ea. | LRA ea. | Pump FLA | MCA | M.O.P | Pump HP | Reservoir Gal. | Fluid Conn. | Water Conn. | Weight Pounds | |
| PZWPT | 9SF5 | 65 | 34 | 42 | 208/230V | 3 | 60Hz | | 10 | 37.2 | 239 | 10.8 | 60 | 90 | 2 | 31 | 1.25" FPT | 1.25" FPT | 800 |
| PZWPT | 9SH5 | | | | 460V | 3 | 60Hz | 1 | | 17.2 | 125 | 2.8 | 25 | 40 | | | | | |
| PZWPT | T9SI5 | | | | 575V | 3 | 60Hz | | | 12.4 | 80 | 1.5 | 20 | 25 | | | | | |

Capacity Table (Refrigerant R407C)

| Model | C | LWT | 105°F Condensing | | | | | |
|-------|------------|------|------------------|-----|------|--|--|--|
| Wodei | Compressor | °F | TONS | KW | EER | | | |
| | ZB76KCE | 42.0 | 9.50 | 8.0 | 13.3 | | | |
| 00 | | 44.0 | 9.92 | 8.1 | 13.9 | | | |
| 98 | | 45.0 | 10.13 | 8.1 | 14.2 | | | |
| | | 50.0 | 11.25 | 8.1 | 15.7 | | | |

Product Dimensional Drawing











