## **PRODUCT DATA SHEET**

Model: **PZWT15D** Packaged Water-Cooled 15 Ton Chiller



Legacy Chiller Systems 851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464



## **Standard Features:**

- ETL listed to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction Accumulator
- · Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- Control circuit fusing
- Condenser(s): Coaxial up to PZW22D
- Compressor motor contactor
- Painted Powder Coated (Most Models), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- Liquid line drier, sight glass, solenoid, TXV
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment
- Extended warranty: See your quote or latest IOM booket revision

#### Tank

- STAINLESS STEEL storage tank with 1/2 inch insulation
- Fused, **STAINLESS STEEL** re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Easy to Use Touch Screen Display on all Legacy Chiller Models



### **Options:**

- Copeland Digital Scroll Compressor
- Remote Idec touchscreen control panel
- Industrial VPN Router
- 5 Port Ethernet Switch
- BacNet Gateway
- Process Pump VFD Controller
- VFD Compressor Control
- 4 year extended compressor warranty
- Casters (factory mounted)
- Condenser water regulating valve
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage Compressor fusion
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI with weather proof cover

#### Tank Options

- Storage tank sight glass
- Tank low liquid level indicator with dry contacts

# **PRODUCT DATA SHEET**

Model: **PZWT15D** Packaged Water-Cooled 15 Ton Chiller



Legacy Chiller Systems 851 Tech Drive Telford, PA 18969

Toll-Free: (877) 988-5464

#### **Dimensional & Electrical Table (Dual Circuit)**

| Chiller<br>Models | Length<br>Inches | Width<br>Inches | Height<br>Inches | Power    |       |       | Compressor |    | RLA  | LRA | Recirculation |     |       | Reservoir | Chiller         | Weight |
|-------------------|------------------|-----------------|------------------|----------|-------|-------|------------|----|------|-----|---------------|-----|-------|-----------|-----------------|--------|
|                   |                  |                 |                  | Voltage  | Phase | Freq. | Qty.       | HP | ea.  | ea. | Pump FLA      | MCA | M.O.P | Gal.      | Fluid<br>Conn.  | Pounds |
| PZWT15DF5         | 85               | 34              | 70               | 208/230V | 3     | 60Hz  | 2          | 9  | 30.1 | 225 | 10            | 60  | 70    | 120       | 1.25"<br>FPT 14 |        |
| PZWT15DH5         |                  |                 |                  | 460V     | 3     | 60Hz  |            |    | 15.5 | 114 | 2.8           | 30  | 40    |           |                 | 1400   |
| PZWT15DI5         |                  |                 |                  | 575V     | 3     | 60Hz  |            |    | 12.1 | 80  | 1.8           | 20  | 25    |           |                 |        |

### Capacity Table (Refrigerant R407C)

| Model | Comproser  | LWT  | 105°F Condensing |      |      |  |  |
|-------|------------|------|------------------|------|------|--|--|
| woder | Compressor | °F   | TONS             | KW   | EER  |  |  |
|       |            | 42.0 | 13.4             | 13.4 | 14.2 |  |  |
| 450   | 700000     | 44.0 | 14.0             | 13.4 | 14.7 |  |  |
| 15D   | ZB66KCE    | 45.0 | 14.4             | 13.4 | 15.0 |  |  |
|       |            | 50.0 | 16.0             | 13.6 | 16.6 |  |  |
|       |            |      |                  |      |      |  |  |

\* = Requires the use of glycol.

