PRODUCT DATA SHEET

Model: **IEZAT7D**


Split-System Air-Cooled
7 Ton Chiller

Legacy Chillers, Inc.
851 Tech Drive
Telford, PA 18969

Toll-Free: (877) 988-5464


with Stainless Steel Tank

R454C Refrigerant



STANDARD ON ALL LEGACY CHILLER MODELS:
Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.

Condenser Model (OC7D)



OC Refrigerant Connections: Discharge Line- 5/8" (2), Liquid Line- 1/2" (2)

Standard Features:

Intertek

- Conforms to UL 60335-2-40:2022 Ed.4
- UL 60335-1:2016 Ed.6
- CSA C22.2 # 60335-1:2016 Ed.2
- CSA C22.2 # 60335-2-40:2022 Ed.4
- **Single Point Power Connection**
- **Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display**
- **STAINLESS STEEL**, brazed plate evaporator
- **Scroll** compressor with crankcase heater
- **Suction Accumulator**
- Liquid line drier, sight glass, solenoid
- Electronic expansion valve
- Manual high pressure cutout
- Tank recirculation pump
- **Water flow switch**
- **Hot Gas Bypass Capacity Control**
- **24V control transformer**
- Control circuit fusing
- Compressor motor contactor
- **Painted - Powder Coated (Most Models), galvanized sheet metal cabinet**
- 1/2" insulation on all water and refrigerant lines
- Complete refrigerant charge from factory
- **Factory Performance Test prior to shipment**

Tank

- **STAINLESS STEEL** storage tank with 1/2 inch insulation
- Fused, **STAINLESS STEEL** re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Options:

- **VFD Compressor Control** on primary compressor
- **Remote Idec touchscreen control panel**
- **5 Port Ethernet Switch**
- **BacNet Gateway**
- **Process Pump VFD Controller**
- 4 year extended compressor warranty
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- Auto city water changeover panel with filter
- Stainless steel, SCH80 PVC or Polypropylene piping fordeionized and reverse osmosis water systems
- Door Mounted HMI weather proof cover

Tank Options

- Storage tank sight glass
- Tank low liquid level indicator with dry contacts
- Auto Tank Fill

© Property of Legacy Chillers, Inc.

PRODUCT DATA SHEET

Model: **IEZAT7D**

Split-System Air-Cooled
7 Ton Chiller

Legacy Chillers, Inc.
851 Tech Drive
Telford, PA 18969

Toll-Free: (877) 988-5464

with Stainless Steel Tank

Dimensional & Electrical Table (Dual Circuit)

Chiller Model	Nominal BTUH	Length Inches	Width Inches	Height Inches	Power			Compressor Qty.	RLA	LRA	Fan Motor		Recirculation Pump FLA	MCA	MOP	Reservoir Gal.	Chiller Fluid Conn.	Weight Pounds	Condenser Model
					Voltage	Phase	Freq.		ea.	ea.	Qty.	FLA ea.							
IEZAT7DE8	78600	75	34	70	208/230	1	60	2	24	132	2	3.8	6.8	68	90	50	1.25 "FPT	1350	OC7D
IEZAT7DF8					208/230	3	60		14.1	115		3.8	6.8	46	60				
IEZAT7DH8					460	3	60		6.7	47.5		1.5	1.5	20	25				
IEZAT7DI8					575	3	60		5.8	40		1.72	1.0	17	20				

Capacity Table (Refrigerant R454C)


Model	COMPRESSOR	AMB (°F)	80			90			95			100			105		
		LWT (°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
7D	YB28KAE	42	6.8	7.1	11.4	6.4	7.8	9.8	6.1	8.1	9.1	5.9	8.5	8.4	5.7	8.9	7.7
		44	7.0	7.1	11.9	6.6	7.8	10.2	6.4	8.1	9.4	6.2	8.5	8.8	6.0	8.9	8.1
		45	7.2	7.1	12.1	6.8	7.8	10.4	6.6	8.1	9.7	6.3	8.5	8.9	6.1	8.9	8.2
		50	7.7	7.1	12.9	7.2	7.8	11.1	7.0	8.2	10.2	6.7	8.5	9.5	6.5	8.9	8.7

1. Capacities on this chart are based on refrigerant R454C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
2. KW input is for compressor(s) only.
3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.

C ETL US LISTED Intertek

Product Dimensional Drawing

R454C Refrigerant



© Property of Legacy Chillers, Inc.